



US009636702B2

(12) **United States Patent**  
**Love, III et al.**

(10) **Patent No.:** **US 9,636,702 B2**  
(45) **Date of Patent:** **May 2, 2017**

(54) **APPARATUS AND METHOD FOR  
CONTROLLED APPLICATION OF LIQUID  
STREAMS TO A SUBSTRATE**

(58) **Field of Classification Search**  
None  
See application file for complete search history.

(71) Applicant: **Milliken & Company**, Spartanburg, SC  
(US)

(56) **References Cited**

(72) Inventors: **Franklin S. Love, III**, Columbus, NC  
(US); **Joseph E. Rumler**, Greenville,  
SC (US); **Mark A. Hornung**,  
Campobello, SC (US); **James C.**  
**Bryant**, Cowpens, SC (US); **Sharon E.**  
**Koh-Fallet**, Simpsonville, SC (US)

U.S. PATENT DOCUMENTS

3,942,342 A 3/1976 Klein et al.  
3,942,343 A 3/1976 Klein  
(Continued)

FOREIGN PATENT DOCUMENTS

EP 0 289 263 11/1988  
EP 0 514 102 11/1992  
GB 1 456 458 11/1976

(\*) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 0 days.

OTHER PUBLICATIONS

Patent Cooperation Treaty PCT International Search Report. Date of  
Mailing: Oct. 27, 2011. International Application No. PCT/US2011/  
043981. International Filing Date: Jul. 14, 2011.

(21) Appl. No.: **15/097,329**

(22) Filed: **Apr. 13, 2016**

(65) **Prior Publication Data**

US 2016/0221030 A1 Aug. 4, 2016

*Primary Examiner* — Nathan T Leong

(74) *Attorney, Agent, or Firm* — Brenda D. Wentz

**Related U.S. Application Data**

(62) Division of application No. 14/533,313, filed on Nov.  
5, 2014, now Pat. No. 9,339,834, which is a division  
of application No. 12/850,166, filed on Aug. 4, 2010,  
now abandoned.

(51) **Int. Cl.**  
**B05B 15/04** (2006.01)  
**B05D 1/02** (2006.01)  
(Continued)

(52) **U.S. Cl.**  
CPC ..... **B05D 1/02** (2013.01); **B05B 1/205**  
(2013.01); **B05B 1/267** (2013.01); **B05B 1/28**  
(2013.01);  
(Continued)

(57) **ABSTRACT**

An improved system for application of liquid streams to a  
substrate. The system incorporates open face flow channels  
for carrying the liquid away from fully enclosed flow  
segments prior to discharge along an unconstrained flow  
path. The present invention further provides an improved,  
self-aligning modular assembly for delivery of impingement  
jet to the liquid streams for diverting the direction of the  
liquid streams. The present invention further provides an  
improved arrangement for collection of the deflected liquid  
in response to application of the impingement jet without  
excess residue build-up.

**6 Claims, 6 Drawing Sheets**

